

# PARAPROJECT®

## Case CC20 CargoCase

Protect , TwinCharge , Transport



Part denomination	PARAPROJECT Case CC20 CargoCase TwinCharge, USB-C®, without cable, black
Part number	6433010399
GTIN /EAN	4006793003064
Field of application	Education
Certificates	CE
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55024
Scope of delivery	<ul style="list-style-type: none"> <li>- 1x Case CC20 CargoCase, with integrated TwinCharge technology</li> <li>- 1x device connecting cable, EU, length: 5m</li> <li>- 1x operating instruction</li> <li>- 1x set of keys (2 pcs)</li> </ul>
Materials	<ul style="list-style-type: none"> <li>- polypropylene</li> <li>- Con-Pearl®</li> </ul>
External dimensions (WxDxH)	600 mm x 400 mm x 340 mm
Weight	9500 g
Transport dimensions	605 mm x 405 mm x 345 mm
Dimensions of euro-pallets	1200 mm x 800 mm x 1740 mm
Number of euro-pallet	12
customs tariff number	42021250
Country of origin	RO
Fittings	<ul style="list-style-type: none"> <li>- case lid: nap foam inlay</li> <li>- case body: TwinCharge charging unit with USB-C and A ports, 20 storage compartments for iPad /tablets</li> <li>- active fans, ventilation openings in the case lid and rear panel for optimal air circulation</li> <li>- temperature sensor, main switch, overvoltage protection</li> </ul>
Compatible devices	all tablets up to 11.5"
Max. number of devices	20
Operating system	iOS / Android / Windows
Cable types for equipment	using customer's own data and charging cables
Power supply	4x TwinCharge modules for the complete power supply of devices
Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 20x iPad / Android tablet with 22W each per port, or 16 x Surface Go 2 tablet with 24W each per port ; USB-C and USB-A output (22 / 30 / 45W): DC ; 5V/9V/12V/15V3A,20V2.25A
Optional accessories	<ul style="list-style-type: none"> <li>- USB charging cable for USB-C to C, USB-C to Lightning, USB-A to Lightning</li> <li>- USB data and charging cable with LED display for USB-C to Lightning , USB-A to Lightning</li> <li>- external week timer</li> </ul>
Lock types	latch mechanism

# PARAPROJECT®

## Case CC20 CargoCase

Protect , TwinCharge , Transport

Connections	- outside: central power supply - inside: 20 x USB-A sockets each or USB-C socket, optional depending on cable types available
Data of currents	- 100 - 240 V - max. 10 A - 50 / 60 Hz
Dimension of pockets	22 x 200 x 270 mm
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm



- active ventilation
- TwinCharge technology



- main switch
- overvoltage protection